WESTON SOLUTIONS, INC.		SOIL BORING LOG					
Project	Turkey Brook	Boring ID	SB-01	Groundwater Levels			
Location	Oakville, Connecticut	Well ID	NA	Date	Depth		
Date Drilled	November 20, 2013	Drilling Method	Direct Push	NA	NA		
Drilling Company	U.S. EPA OEME*	Sampling Method	4-ft. Macrocore				
Operator	Jerry Keefe/Dan Granz	Completion Depth	12 feet bgs				
Drill Rig	Geoprobe	Surface Elevation	NA				
Logged by	George Mavris - Weston, Superfund Technical Assessment and Response Team (START)						
Donath (ft has)	Macrocore Recovery	Call Dannintian (D	Soil Description (Burmistor System) PID Screen				

			<u> </u>		
Depth (ft bgs)	Macrocore Number	Recovery (inches)	Soil Description (Burmister System)		
1_ 2_ 3_ 4_	1	28	 0 - 2" Dark brown, fine SAND and SILT, trace roots (topsoil). Moist. 2 - 21" Dark brown, fine-to-medium SAND, trace fine gravel (coal-like fragments and metal), silt, and roots. Moist. [Fill]. 21 - 24" Grayish-white, fine GRAVEL, little medium sand. Dry. [Fill]. 24 - 28" Dark brown, fine SAND, trace fine gravel and silt. Moist. [Fill]. 	Top = 0 Bottom = 0 Length = 0	
 5_ 6_ 7_ 8_	2	34	0 - 1" Grayish-brown, fine SAND, trace fine gravel. Moist. [Fill]. 1 - 5" *** Black, fine SAND, trace silt. PID = 0.6 ppm. No odor. [Fill]. 5 - 20" Reddish-brown and blackish-brown, fine-to-coarse SAND, some coarse-to-fine gravel (SubA), trace silt. Very moist. [Fill]. 20 - 23" Light gray, coarse GRAVEL (SubA, granitic). Dry. [Fill]. 23 - 30" Same as 5 to 20-inch interval. 30 - 34" Same as 20 to 23-inch interval.	Top = 0 Bottom = 0 Length = 0.6	
9_ 10_ 11_ 12_	3	46	0 - 6" Brown, fine GRAVEL, some coarse-to-medium sand, trace silt. Very moist. [Fill]. 6 - 46" Brown, fine-to-medium SAND, little fine gravel, trace silt. Very tight. [Fill].	Top = 0 Bottom = 0 Length = 0	

Notes:

bgs = below ground surface ft = feet ppm = parts per million NA = Not Applicable SubA = subangular PID = Photoionization Detector PROPORTIONS USED

(BY DRY WEIGHT)

0 to 10% = Trace

>10 to 20% = Little

>20 to 35% = Some

>35 to 50% = And

>50% = Major

Analytical results for Total Petroleum Hydrocarbons (C9 - C36) = 300 milligrams per kilogram (mg/Kg).

^{*} United States Environmental Protection Agency, Office of Environmental Measurement and Evaluation ** MultiRAE Plus Systems multi-gas photoionization detector calibrated to 100 ppm isobutylene, 50 ppm carbon monoxide, 25 ppm hydrogen sulfide, 20.9% oxygen, and 50% methane.

^{***} Soil sample SB-01 collected from 1 to 5-inch interval from Macrocore No. 2 (4 - 8 feet). PID = 0.6 ppm.